


LENSTAR LS 900 Improving outcomes



02 | 03 **LENSTAR LS 900**

LENSTAR Outstanding optic measurement results

While the introduction of optical biometry revolutionized cataract surgery in the late 1990s, Haag-Streit is writing the latest chapter in biometry history with its Lenstar LS 900.

The Lenstar provides highly accurate laser optic measurements for every section of the eye – from the cornea to the retina – and is the first optical biometer on the market that can measure the thickness of the crystalline lens. With its integrated Olsen¹ formula and the optional Toric Planner featuring the Barrett Toric Calculator¹², the Lenstar provides the user with latest technology in IOL prediction for any patient.

Dual zone keratometry, with 32 measurement locations or topography measurement with the optional T-Cone, provides reliable and precise measurements for the K values, axis, and astigmatism that are essential to the sophisticated planning of toric lenses^{2,3}. The Lenstar LS 900 offers the optimal planning platform for superior refractive outcomes in cataract surgery, both now and in the future.



Measured lens thickness – improved refractive outcomes⁴

With its integrated Olsen¹ IOL calculation formula and the Lenstar's unique measurement of the lens thickness, accurate prediction of the IOL position is provided for every type of eye. To improve refractive outcomes, the Lenstar is the optimal choice.

Perfect K values – best toric results


The Lenstar features dual zone keratometry or T-Cone topography for precise astigmatism and axis measurement^{2,3}. The integrated Barret Toric Calculator predicts toric IOL, considering the posterior cornea for best refractive outcomes.

For post-refractive cases – quick and reliable

Shammas and Masket IOL calculation methodologies can be used for post-refractive patients even without any clinical history available ^{5,6}.

04 | 05 **EXPERT OPINION**

LENSTAR an excellent choice for toric and premium channel IOL



LENS THICKNESS MATTERS

Improve your refractive outcomes with measured lens thickness.

Precise measurement of the entire eye – from cornea to retina – is key to achieving optimal IOL prediction accuracy in surgery.

The Lenstar is the first optical coherence biometer to provide the surgeon with all the measurements necessary to take full advantage of the latest IOL prediction methods, such as the Holladay 2 and Olsen¹ formulae, now integral to the Lenstar. Furthermore, it is ready to meet your requirements for future multi-variable formulae. With the optional EyeSuite Toric Planner featuring the Barrett Toric Calculator¹², the Lenstar enables intuitive and accurate planning of astigmatic cases. Operation sketches based on high resolution images of the patient's eye complete this sophisticated planning tool.

Lenstar measurements include central corneal thickness, anterior chamber depth, lens thickness, axial length, keratometry, white-to-white distance and pupil diameter.

DUAL ZONE KERATOMETRY OR T-CONE TOPOGRAPHY

Precise measurements and intuitive planning – best toric results.

Lenstar's unique dual zone keratometry provides measurement of the axis and astigmatism, equivalent to the "Gold Standard" manual keratometry^{2,3} recommended for toric IOL by manufacturers.

The closely spaced 32 measurement point pattern improves precision, both delivering more data and minimizing the need for software data interpolation


Optionally, the Lenstar can be equipped with the T-Cone topography add-on. That feature not only enables axis and astigmatism measurement but also offers full topography maps of the central 6 mm optical zone. In addition to topography, EyeSuite IOL also now features a toric IOL planning platform that is included with the T-Cone.


QUICK AND RELIABLE BIOMETRY FOR ALL EYES

Fast, precise and comprehensive for better refractive results.

The measurement process of the Lenstar is fast and optimized to ensure maximum patient comfort – users report five scans of both eyes in three minutes or less, optional the Automated Positioning System (APS) features dynamic eye-tracking allowing easy automated measurement acquisition with a single click. The Dens Cataract Measurement (DCM) Mode ensures state-of-the-art cataract penetration. Each of the measurements can be validated for efficacy and adjusted, if necessary, to ensure complete biometry accuracy.

In addition to the Olsen, Barrett and standard IOL calculation formulae Eye-Suite IOL provides the user with a set of premium IOL calculation formulae for post-keratorefractive patients. The Shammas No-History and Masket formulae have both proven their efficacy in several peer-reviewed studies and may be regarded as best-in-class^{5,6}.








06 | 07 LENSTAR MEASUREMENTS


Complete optical biometry The all-in-one optical biometer and IOL planning platform

Optical coherence biometry has revolutionized cataract surgery. Featuring OLCR technology, Lenstar is redefining optical coherence biometry.

Cutting-edge, multivariable IOL calculation formulae, such as the Olsen, Barrett or Holladay 2 formula for sophisticated IOL calculation, demand more than just the axial length and keratometry measurement. Lenstar provides all the key biometric parameters simultaneously.

In a single measurement scan and using optical low coherence reflectometry (OLCR), Lenstar captures axial dimensions of all of the human eye's optical structures. Additionally, Lenstar measures corneal curvature, white-to-white and more.





Central corneal thickness cct

As for every other Lenstar axial measurement, optical coherence biometry is used to measure CCT with stunning reproducibility of $\pm 2\,\mu\text{m}$. CCT is a key parameter in glaucoma diagnosis, and is also used for laser refractive surgery and/or to differentiate prior myopic or hyperopic LASIK procedures when there is no patient history.

Keratometry */ Topography *Topography *Top

Lenstar's unique dual zone keratometry, featuring 32 marker points, provides perfect spherical equivalent⁷, magnitude of astigmatism and axis position^{2,3}, making it the biometer of choice for toric IOL's. With the optional T-Cone topography add-on, Lenstar provides full topography maps of the central 6 mm optical zone that are crucial for cataract planning.

White-to-white wtw

Based on high-resolution color photography of the eye, every white-to-white measurement can be reviewed and adjusted by the user if necessary. As such, it is fully reliable for use with anterior chamber and sulcus-fixated phakic IOLs. It can also be used to determine advanced IOL calculation formulae.

Pupillometry PD

Measurement of the pupil diameter in ambient light conditions can be used as an indicator for the patient's suitability for apodized premium IOLs, as well as for laser refractive procedures.

Lens thickness LT

Accurate measurement of the lens thickness is key to optimal IOL prediction accuracy when using the latest IOL calculation formulae, Olsen or Holladay 2. Measuring the lens thickness with Lenstar significantly improves the IOL prediction accuracy of Holladay 2 and leads to a different IOL power selection in 30% of cases⁴.

Anterior chamber depth ACD

Like all axial dimensions captured by the Lenstar, ACD is measured by optical coherence biometry, providing more precision and reproducibility ⁷. This allows ACD to be measured on phakic as well as on pseudophakic eyes⁸. Additionally, the Lenstar is able to display the anatomical anterior chamber depth (endothelium to anterior lens surface).

Axial length AL

OLCR technology, using a superluminescent diode as the laser source, enables measurement of the axial length of the patient's eye, precisely on the patient's visual axis and in the presence of dense media.

The user can review and move all of the measuring gate positions on the A-scan if necessary.

The Lenstar A-scan appears very similar to an immersion ultrasound scan, for easy user interpretation. The advanced digital signal processing used with the Dens Cataract Measurement (DCM) mode provides cutting-edge performance with respect to penetration rates.

Special eye conditions

All of the described measurements are available for use on the regular eye, as well as for aphakic, pseudoaphakic and silicone oil-filled eyes. In case of error, users may even change the selected eye condition after completion of the measurement procedure.

08 | 09 **IOL CALCULATION**


Intuitive and efficient The ultimate platform for toric IOL planning

Lenstar features a unique dual zone keratometer with a total of 32 marker points on two concentric rings of 1.65 and 2.3 mm in diameter for improved refractive outcomes with toric lenses^{2,3}. It has now been complemented with an optional T-Cone topography add-on and the optional toric surgery planning platform EyeSuite IOL Toric Planner. The T-Cone enables the Lenstar to provide true Placido topography of the central 6mm optical zone. The toric surgery planning platform allows planning and optimization of the surgical procedure based on high-resolution and true color eye images taken with the Lenstar, either in combination with the T-Cone, or simply based on the dual zone keratometry of the standard unit. The toric planner shows the implantation axis, the incision location and user-defined guiding meridians in the real patient image. Calculation of the toric IOL performed with the Barrett Toric Calculator, considers the front and back surface of the cornea as

well as lens shape for optimum calculation results. The Barrett Toric Calculator demonstrated its superiority in studies¹² and is the choice of the ASCRS as well as the APACRS for their on-line toric calculators.

Incision optimization tools allow for precise placement of the incision to minimize the residual astigmatism based on the surgically induced astigmatism. Alternatively, the incision location is fixed and the optimal toric IOL is provided.

Planning of the operation on real eye images allows the user to define recognizable, additional guiding lines to anatomical landmarks in the intraoperative view. They either serve as a base line point for the intraoperative orientation or as a fallback strategy if external marking is not successful. The planning sketch can easily be printed and hung near the microscope.



T-CONE

Topography for torics – match the axis

With the optional T-Cone toric platform, the axis and astigmatism measurement of Lenstar is extended with true 11-ring Placido topography. This additional data improves the efficacy and safety of toric IOL surgery, eliminating the risk of irregularities and allowing the user to double check the axis location on the topography maps as well as in the surgical planning sketch on high resolution images of the patient's eye. The T-Cone is combined with the EyeSuite IOL Toric Planner for optimal planning of the intervention based on the Barrett Toric Calculator.

OLSEN

Get the IOL position right – every time


Estimating the postoperative IOL position is the key aim, but also the proverbial Achilles heel, of any IOL calculation formula. With its unique concept of the C-Constant, the Olsen formula calculates the postoperative lens position as a fraction of the crystalline lens thickness and the ACD. This approach allows accurate calculation of the lens position independent of the corneal status of the eye. The lens position is then used to calculate the IOL power based on ray tracing, the same technology used to design telescopes and camera lenses.


POST-REFRACTIVE IOL CALCULATION

Shammas No-History and Masket – for premium results

The Lenstar EyeSuite software provides the user with a comprehensive set of cutting-edge IOL calculation formulae for normal eyes. IOL Power calculation in patients with prior LASIK or PRK, presenting with no history, is easily achieved with the on-board Shammas No-History method.^{5,6} If the change in refraction is known, then the Masket and modified Masket formulae⁵ may also be used.








Connectivity is key **Open data and intuitive user interfaces for optimal workflow**

The EyeSuite software is designed for optimal patient flow in busy practices. Paired with Lenstar's one scan – get all measurements technology and the Automated Positioning System APS biometry acquisition is fast.

Sophisticated capture and analysis algorithms – as well as the possibility to review the raw data of every parameter in detail to ensure correct measurement – result in full transparency and confidence that the biometry is accurate and precise.

With EyeSuite software, Lenstar is fully networkable and allows full real-time access to all data in a practice. Surgeons can check their biometry results or recalculate an IOL even in the OR.

Further, the EyeSuite Script Language or standardized interfaces, such as GDT or DICOM, connect easily to almost any electronic medical record system. And EyeSuite's open data interface, combined with Lenstar's separate computer, allows autopopulation of the data fields in the latest fourth generation calculation tools – such as Holladay 2, the Holladay toric calculator (Holladay IOL Consultant) and Olsen (PhacoOptics). This not only saves valuable staff time, it also eliminates the risk of transcription errors.



Your choice

Lenstar family and options, get the right tool for your needs

The Lenstar is now available in two basic versions: Lenstar Essential and Lenstar Pro.

The Lenstar Essential, provides all basic functionalities of a stand-alone optical biometer for standard cataract care in a busy practice. As such the Lenstar Essential features the unique Automated Positioning System (APS) as a standard, allowing automatic measurement acquisitions at a single click. A Lenstar Essential may be upgraded on site to Pro at any time, offering the full range of functionality of the Pro version and access to all options available.

The Lenstar Pro features latest IOL calculation methodologies and more, for advanced technology IOL planning and allows access to all options like the T-Cone Toric Platform or the EyeSuite IOL Toric Planner. Furthermore it provides the user with full control over all raw measurements for quality check and with the

possibility to easily export any measurement data for research purposes. Networkability is another feature of the Pro version allowing access to the measurements and IOL calculation from any PC in the practice.

Options to the LENSTAR Pro are the T-Cone Toric Platform, providing true Placido Topography of the central 6 mm of the cornea for the comprehensive planning of toric IOL, combined with the EyeSuite IOL Toric Planner, which is available as an independent option as well. The Toric planner enables the user to calculate the toric IOL based on the Barrett Toric Calculator and to draw operation sketches based on high resolution eye images of the patient. The sketches feature axis of implantation, flat and steep meridian of the cornea, incision location and size, as well as location of user selected anatomic landmarks for accurate transfer of the plan to surgery.



		Lenstar Essential	Lenstar Pro
Operation	Multi user system		
	Dense Cataract Measurement Mode (DCM)		
	Automated Positioning System (APS)		0
Measurements	Axial length (AL)		
	Central corneal thickness (CCT)		
	Anterior chamber depth (ACD)		
	Anatomic ACD (AD)		
	Lens thickness (LT)		
	Keratometry (K)		
	Topography (Topo)		0*
	White to white (WTW)		
	Pupillometry (PD)		
Quality control	Display of standard deviation of repeated measurements	=	-
	Access to A-scan and imaging data		
	Manual adjustments of measurement gates		
IOL Calculation	Barrett Universal II		
	Barrett Toric Calculator		0**
	Haigis		
	HofferQ		
	Holladay 1		
	Olsen		
	SRK II and SRK/T		
	Masket / Modified Masket		
	Shammas No-History		
OL constants	Personalisation of IOL constants		
Networkability	Electronic medical record interfaces (EyeSuite Script Language, GDT, EyeSuite Command Line Interface)	-	
	DICOM (SCU)	0	0
	IOL calculation on additional workstations		
	EyeSuite viewing stations		
	■ included	O optionally available	

to Pro, which is possible on site at any time

O* This option is part of the T-Cone Toric Platform

O** This option is part of the T-Cone Toric Platform or the EyeSuite IOL Toric Planner

Technical specifications Lenstar LS 900®

Measured variables and modes

Corneal thickness ct

Measurement range 300 – 800 μm Display resolution 1 μm

Anterior chamber depth ACD

Measurement range 1.5 – 6.5 mm Display resolution 0.01 mm

Lens thickness LT

Measurement range 0.5 – 6.5 mm Display resolution 0.01 mm

Axial length AL

Measurement range 14 – 32 mm Display resolution 0.01 mm

White-to-white distance wtw

Measurement range 7 – 16 mm Display resolution 0.01 mm

Keratometry^K

Measurement range
for radius 5 – 10.5 mm
Display resolution 0.01 mm
Measurement range
for axis angle
Display resolution 1°

Pupillometry PD

Measurement range 2 – 13 mm Display resolution 0.01 mm

Measurement modes

'Normal' eye Aphakic eye Pseudophakic eye Silicone-filled eye Combination of the above

Laser safety

Class 1 laser product

Onboard IOL calculation formulae

Barrett Universal II, Barrett Toric Calculator*, Haigis, HofferQ, Holladay 1, Olsen, SRK/T, SRK II, Masket, Modified Masket, Shammas No-History

IOL calculation data interfaces

- Holladay IOL Consultant Professional Edition (Holladay 2 formula and Holladay toric calculator)⁹
- · PhacoOptics (Olsen formula)10
- Okulix (Ray-Tracing by Prof. Preussner)¹¹

Electronic medical record system interfaces

- · DICOM (SCU)
- · EyeSuite Script Language
- · GDT
- · EyeSuite command line interface

LENSTAR LS 900® Optical Biometer Indications for Use

The Lenstar LS 900 Biometer is a non-invasive, non-contact OLCR (Optical Low Coherence Reflectometry) device. It is used for obtaining ocular measurements and performing calculations to assist in the determination of the appropriate power and type of IOL (intraocular lens) for implantation after removal of the natural crystalline lens following cataract removal.

The LENSTAR LS 900® measures:

- · Axial eye length
- · Corneal thickness
- $\cdot \ \text{Anterior chamber depth} \\$
- · Aqueous depth
- $\boldsymbol{\cdot}$ Lens thickness

- · Corneal curvature
- · Radii for flat and steep meridian
- · Axis of the flat meridian
- · White-to-white distance
- · Pupil diameter

^{*}Barrett Toric Calculator is part of the optional EyeSuite IOL Toric Planner.
The above-mentioned measurement ranges are based on the standard settings of the device for automatic measurement and analysis.

¹ Olsen T. Improving IOL power Calculation by measurement of the lens thickness with the Lenstar LS900 presented at the ESCRS in Paris 2010. 2 Hill W, Osher R, Cooke D, Solomon K, Sandoval H, Salas-Cervantes R, Potvin R. Simulation of toric intraocular lens results: manual keratometry versus dual zone automated keratometry from an integrated biometer. J Cataract Refract Surg. 2011 Dec; 37(12): 2181-7. 3 Gundersen KG, Potvin R. Prospective study of toric IOL outcomes based on the Lenstar LS 900® dual zone automated keratometer. BMC Ophthalmol. 2012 Jul 16; 12:21. 4 Lam S. Comparison of Age-derived Lens Thickness to Optically Measured Lens Thickness in IOL power Calculation: A Clinical Study. J Refract Surg. 2012 Feb; 28(2): 154-5. 5 Wang L, Hill WE, Koch DD. Evaluation of intraocular lens power prediction methods using the American Society of Cataract and Refractive Surgeons Post-keratorefractive Intraocular Lens power Calculator. J Cataract Refract Surg. 2010 Sep; 36(9): 1466-73. 6 McCarthy M, Gavanski GM, Paton KE, Holland SP. Intraocular lens power calculations after myopic laser refractive surgery: a comparison of methods in 173 eyes. Ophthalmol. 2009, 2011 May; 118(5): 940-4. 7 Buckhurst PJ, Wolffsohn JS, Shah S, Naroo SA, Davies LN, Berrow EJ. A new optical low coherence reflectometry device for ocular biometry in cataract patients. Br J Ophthalmol. 2009 Jul; 93(7): 949-53. 8 Olsen T. Use of fellow eye data in the calculation of intraocular lens power for the second eye. Ophthalmol. 2009 Jul; 93(7): 949-53. 8 Olsen T. Use of fellow eye data in the calculation of intraocular lens power for the second eye. Ophthalmol. 2013 Sep; 118(9): 1710-5. 9 http://www.hicsoap.com/accessed March 16, 2015 11 http://www.hicsoap.

Members of HAAG-STREIT Group

HAAG-STREIT Holding AG www.haag-streit-holding.com

www.haag-streit.de

HAAG-STREIT Deutschland GmbH

HAAG-STREIT AG www.haag-streit.com IPRO GmbH www.ipro.com

SPECTROS AG www.spectros.ch

CLEMENT CLARKE Ltd. www.clement-clarke.com

HAAG-STREIT Medtech AG www.haag-streit-medtech.com HAAG-STREIT UK www.haag-streit-uk.com

HAAG-STREIT France EURL www.haag-streit.fr

John Weiss Ltd. www.johnweiss.com

HAAG-STREIT Far East www.haag-streit-fareast.com HAAG-STREIT USA www.haag-streit-usa.com

HAAG-STREIT Surgical GmbH www.haag-streit-surgical.com

Reliance Medical Inc. www.haag-streit-usa.com

Möller-Wedel GmbH & Co KG www.moeller-wedel.com

Asetronics AG www.asetronics.ch

Möller-Wedel Optical GmbH www.moeller-wedel-optical.com ComLab AG www.comlab.ch

HAAG-STREIT AG

Gartenstadtstrasse 10 3098 Koeniz Switzerland Phone +41 31 978 01 11 Fax +41 31 978 02 82 info@haag-streit.com www.haag-streit.com

